


Lithium Iron Phosphate (LiFePO4) Battery Specification

SLAUMXLI100-12DIN (12.8V100AH)




● Outer dimensions (mm)



● Specifications

Nominal voltage	12.8V	
Typical capacity	100Ah	At 0.2C discharge rate
Max continuous discharge current	100A	
Peak discharge current	300A	1s
Over current protection	500±20A	10ms
Discharge cut-off voltage	8V	
Charge voltage	14.6±0.1V	Charge mode: CC/CV, Use a constant current, constant voltage(CC/CV) please use special lithium charger.
Charge current	≤ 100A	DO NOT REVERSE!
Inner resistance	≤ 10mΩ	Between positive and negative polar
Operation temperature range	Charge	0°C ~ +45°C
	Discharge	-20°C ~ +60°C When the environment temperature is higher than 45°C, please pay attention to ventilation and heat rejection.
Storage temperature range	0°C ~ 40°C (Capacity 80%)	Recommended long-term storage temperature is 15~25°C
Humidity	≤ RH≤85%	
Shell material	ABS plastic	
Weight	About : 12.0Kg	
Size (L*W*H)	353*175*190mm ±1mm	
Protection function	Over charge protection, Over discharge protection, Over current protection, Balance function, Temperature protection	
Communication (optional)	N/A	

● Terminal Type (mm)



● Characteristics

